

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

1 Identification

- **Product identifier**
- **Trade name: Lightning Strip Wood**
- **Article number:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Lacquer solvent/ Varnish thinner
- **Restrictions on use:** Contact manufacturer.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Real Products Mfg., Ltd.
3480 State Route 15
Ney, OH 43549
(419) 658-2333
lightning@realproductsmfg.com
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT SE 1 H370 Causes damage to the central nervous system and optic nerve.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Additional information:**

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of ingredient(s) of unknown toxicity.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 1)

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS06 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

methanol
dichloromethane
2-aminoethanol

- **Hazard statements**

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H351 Suspected of causing cancer.
H370 Causes damage to the central nervous system and optic nerve.

- **Precautionary statements**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist/vapors/spray.
P264 Wash thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P330 Rinse mouth.
P302+P352 If on skin: Wash with plenty of water.
P361+P364 Take off immediately all contaminated clothing and wash it before reuse.
P405 Store locked up.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH	3	Health = *3
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

* - Indicates a long term health hazard from repeated or prolonged exposures.

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

75-09-2	dichloromethane ☠ Carc. 2, H351	50-100%
67-56-1	methanol ☠ Flam. Liq. 2, H225 ☠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 ☠ STOT SE 1, H370	10-25%
141-43-5	2-aminoethanol ☠ Skin Corr. 1B, H314 ☠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335 Flam. Liq. 4, H227	< 5%
9016-45-9	4-nonylphenyl-polyethylene glycol ☠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	< 5%

· Additional information:

For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
Provide oxygen treatment if affected person has difficulty breathing.
In case of irregular breathing or respiratory arrest provide artificial respiration.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 3)

If skin irritation continues, consult a doctor.

- **After eye contact:**

Protect unharmed eye.

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed**

Headache

Breathing difficulty

Coughing

Dizziness

Acidosis

Frostbite

Vision disorders.

Irritant to skin and mucous membranes.

Strong irritant with the danger of severe eye injury.

Nausea in case of ingestion.

Gastric or intestinal disorders when ingested.

Disorientation

Unconsciousness

- **Danger**

Toxic if swallowed, in contact with skin or if inhaled.

Danger of impaired breathing.

Danger of pulmonary edema.

Danger of pneumonia.

Causes serious eye damage.

Danger of convulsion.

Vapors have narcotic effect.

Suspected of causing cancer.

Causes damage to the central nervous system and optic nerve.

- **Indication of any immediate medical attention and special treatment needed**

Contains methanol, methylene chloride. Consult literature for specific antidotes.

Medical supervision for at least 48 hours.

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

Water fog / haze

Alcohol resistant foam

Carbon dioxide

Gaseous extinguishing agents

Fire-extinguishing powder

- **For safety reasons unsuitable extinguishing agents:**

Water stream.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 4)

Water spray

- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information**
Eliminate all ignition sources if safe to do so.
Cool endangered receptacles with water fog.
Use large quantities of foam as it is partially destroyed by the product.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Ensure adequate ventilation.
Use personal protective equipment as required.
- **Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
Dispose contaminated material as waste according to item 13.
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Prevent formation of aerosols.
Use only in well ventilated areas.
Avoid splashes or spray in enclosed areas.
- **Information about protection against explosions and fires:**
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Provide ventilation for receptacles.
Store only in the original receptacle.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 5)

Store away from oxidizing agents.

Do not store together with alkalis (caustic solutions).

- **Further information about storage conditions:** Keep containers tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

75-09-2 dichloromethane

PEL (USA)	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 174 mg/m ³ , 50 ppm BEI
EL (Canada)	Long-term value: 25 ppm IARC 2B
EV (Canada)	Long-term value: 175 mg/m ³ , 50 ppm
LMPE (Mexico)	Long-term value: 50 ppm A3, IBE

67-56-1 methanol

PEL (USA)	Long-term value: 260 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV (USA)	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI
EL (Canada)	Short-term value: 250 ppm Long-term value: 200 ppm Skin
EV (Canada)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
LMPE (Mexico)	Short-term value: 250 ppm Long-term value: 200 ppm PIEL, IBE

141-43-5 2-aminoethanol

PEL (USA)	Long-term value: 6 mg/m ³ , 3 ppm
REL (USA)	Short-term value: 15 mg/m ³ , 6 ppm Long-term value: 8 mg/m ³ , 3 ppm

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 6)

TLV (USA)	Short-term value: 15 mg/m ³ , 6 ppm Long-term value: 7.5 mg/m ³ , 3 ppm
EL (Canada)	Short-term value: 6 ppm Long-term value: 3 ppm
EV (Canada)	Short-term value: 15 mg/m ³ , 6 ppm Long-term value: 7.5 mg/m ³ , 3 ppm
LMPE (Mexico)	Short-term value: 6 ppm Long-term value: 3 ppm

· **Ingredients with biological limit values:**

75-09-2 dichloromethane

BEI (USA)	0.3 mg/L Medium: urine Time: end of shift Parameter: Dichloromethane (semi-quantitative)
-----------	---

67-56-1 methanol

BEI (USA)	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----------	---

· **Additional information:** No further relevant information available.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

· **Engineering controls:** Provide adequate ventilation.

· **Breathing equipment:**

NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

· **Protection of hands:**



Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

PVA gloves

· **Not suitable are gloves made of the following materials:**

Nitrile rubber, NBR

Neoprene gloves

PVC gloves

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 7)

- **Eye protection:**
Contact lenses should not be worn.



Safety glasses

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment** Avoid release to the environment.
- **Risk management measures** See Section 7 for additional information.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - **Form:** Liquid
 - **Color:** Colorless
- **Odor:** Pungent
- **Odor threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**
 - **Melting point/Melting range:** Undetermined.
 - **Boiling point/Boiling range:** 40 °C (104 °F) (DCM)
- **Flash point:** Not applicable.
- **Flammability (solid, gaseous):** Not applicable.
- **Auto-ignition temperature:** Not determined.
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
 - **Lower:** Not determined.
 - **Upper:** Not determined.
- **Oxidizing properties** Non-oxidizing.
- **Vapor pressure at 20 °C (68 °F):** 340 mmHg
- **Density at 20 °C (68 °F):** 1.2 g/cm³ (10.014 lbs/gal)
- **Relative density** Not determined.
- **Vapour density at 20 °C (68 °F)** >1 g/cm³ (>8.345 lbs/gal) (air=1)
- **Evaporation rate at 20 °C (68 °F)** >1 (butyl acetate=1)
- **Solubility in / Miscibility with**
 - **Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 8)

- **Viscosity:**
- Dynamic:** Not determined.
- Kinematic:** Not determined.
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with strong oxidizing agents.
Reacts with strong alkali.
Toxic fumes may be released if heated above the decomposition point.
Reacts with certain rubbers and/or plastics.
Reacts with certain metals.
- **Conditions to avoid** Store away from oxidizing agents.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Formaldehyde
Hydrogen chloride (HCl)
Phosgene

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

75-09-2 dichloromethane

Oral	LD50	> 2000 mg/kg (rat)
Inhalative	LC50/4h	88 mg/l (rat)

141-43-5 2-aminoethanol

Oral	LD50	2050 mg/kg (rat)
Dermal	LD50	1000 mg/kg (rabbit)

9016-45-9 4-nonylphenyl-polyethylene glycol

Oral	LD50	4290 mg/kg (mouse)
------	------	--------------------

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
Danger through skin absorption.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 9)

Toxic and/or corrosive effects may be delayed up to 24 hours.

· **Carcinogenic categories**

· **NTP (National Toxicology Program)**

75-09-2	dichloromethane	R
---------	-----------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

75-09-2	dichloromethane
---------	-----------------

· **Probable Routes of Exposure**

Ingestion.

Inhalation.

Eye contact.

Skin contact.

· **Acute effects (acute toxicity, irritation and corrosivity):**

Toxic if swallowed, in contact with skin or if inhaled.

Causes serious eye damage.

Irritating to skin.

Causes damage to the central nervous system and optic nerve.

· **Repeated Dose Toxicity:** Danger of very serious irreversible effects.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**

Carc. 2

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Suspected of causing cancer.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** Causes damage to the central nervous system and optic nerve.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

9016-45-9 4-nonylphenyl-polyethylene glycol	
LC50	1.821 mg/l (daphnia) (48 h)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:**

Harmful to fish

Toxic for water fleas

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: **Lightning Strip Wood**

· **Other adverse effects** No further relevant information available.

(Contd. of page 10)

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Incinerate in accordance with local, state and federal regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN2810

· **UN proper shipping name**



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

· **DOT**

Toxic, liquids, organic, n.o.s. (Dichloromethane, Methanol)

· **ADR**

2810 TOXIC LIQUID, ORGANIC, N.O.S. (DICHLOROMETHANE, METHANOL)

· **IMDG, IATA**

TOXIC LIQUID, ORGANIC, N.O.S. (DICHLOROMETHANE, METHANOL)

· **Transport hazard class(es)**

· **DOT**



· **Class**

6.1 Toxic substances

· **Label**

6.1

· **ADR**

· **Class**

6.1 (T1) Toxic substances

· **IMDG, IATA**



· **Class**

6.1 Toxic substances

· **Label**

6.1

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 11)

· Packing group	III
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Toxic substances
· Danger code (Kemler):	60
· EMS Number:	F-A,S-A
· Segregation groups	Liquid halogenated hydrocarbons
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN2810, Toxic, liquids, organic, n.o.s. (Dichloromethane, Methanol), 6.1, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

75-09-2 dichloromethane

67-56-1 methanol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California)

· Chemicals known to cause cancer:

75-09-2 dichloromethane

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

67-56-1 methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

75-09-2 dichloromethane

L

· IARC (International Agency for Research on Cancer)

75-09-2 dichloromethane

2B

· TLV (Threshold Limit Value established by ACGIH)

75-09-2 dichloromethane

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

75-09-2 dichloromethane

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 12)

· **State Right to Know Listings**

None of the ingredients is listed.

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

75-09-2	dichloromethane
---------	-----------------

· **Canadian Ingredient Disclosure list (limit 1%)**

67-56-1	methanol
---------	----------

141-43-5	2-aminoethanol
----------	----------------

· **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 07/29/2015 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· **Sources**

Website, European Chemicals Agency (<http://http://echa.europa.eu/>)

Website, US EPA Substance Registry Services (<http://http://ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do>)

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/29/2015

Reviewed on 07/29/2015

Trade name: Lightning Strip Wood

(Contd. of page 13)

Website, Chemical Abstracts Registry, Ammerican Chemical Society (<https://www.cas.org>)

Patty's Industrial Hygiene, 6th ed. , Rose, Vernon, ed. ISBN: ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com